



Specifications Sylvania LED Downlight  
Insaver Slim 205 Aluminium White  
20W 2350lm 70D - 830 Warm White |  
Cutout 205mm - IP44 - Dimmable

[View Product](#)

General Information

|                          |                             |
|--------------------------|-----------------------------|
| SKU                      | 255246                      |
| EAN                      | 5410288305387               |
| Brand                    | Sylvania                    |
| Manufacturer Name        | INSV SL U19 IP44 DL 205 830 |
| Any Lamp all-in warranty | 5 Years                     |
| Average Lifetime (h)     | 100000                      |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Emergency Lighting          | No Emergency Unit  |
| Tiltable                    | No                 |
| Technology                  | LED Integrated     |
| Replaces (Watt)             | 2x18               |
| Wattage                     | 20                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Dimmable with Dali |
| Colour Code                 | 830 Warm White     |
| Colour temperature (Kelvin) | 3000 Warm White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 70                             |
| Luminous Flux (Lumen)    | 2350                           |
| Luminous Efficacy (lm/W) | 117.5                          |
| Power factor             | >0.93                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 205                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK07 - 2 joules        |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 60  |
| Diameter (mm) | 220 |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process